


PIPE/TUBE CUTTING & PREPARATION

X-CEL® Means Speed

Many of our most popular tubing cutters now include several X-CEL features to make your job quicker and easier.

- X-CEL Knob – cut tubing more quickly and easily with our larger, more ergonomic designs.
- X-CEL Wheel Pin – change your cutter wheel quickly using our new ball detent design...no tool needed...no lost clips!
- Spare cutter wheels included for maximum uptime.



Enclosed Feed Tubing Cutters with New X-CEL Features

- Telescoping feed screw design keeps the cutter at the same length regardless of tubing diameter – good for tight spaces.
- Features an enclosed feed screw to eliminate clogging and jamming, grooved rollers for close-to-flare cuts, and a fold-away reamer.
- Now includes X-CEL Knob and X-CEL Pin for quicker cutting and wheel replacement.
- Made from high-strength zinc alloy.
- Spare cutter wheel included in the knob.
- Cuts hard / soft copper, aluminium, brass and multilayer tubes.
- Model 205 / 205S have quick acting mechanism for faster size adjustments.



Catalog No.	Model No.	Description	Std. Wheel	Capacity		Weight		Std. Pack
				mm	lb.	kg		
For Copper Tubing								
66737	150L	Enclosed Feed Cutter	E-3469	6 - 35	1	0,44	6	
33055	205*	Ratcheting Encl. Feed Cutter	E3469	6 - 60	2	0,91	1	
For Steel Tubing								
66742	150LS	Above with Heavy Duty Wheel	E4546	6 - 35	1½	0,47	6	
33070	205S**	Above with Heavy Duty Wheel	E-4546	6 - 60	2	0,91	1	

* Model 205 has an additional quick-acting mechanism

** Model 205S is suitable for stainless steel.

Screw Feed Tubing Cutters with New X-CEL Features

- Clean, square cuts are easily made on copper, brass, aluminum and thin-wall steel.
- Now includes X-CEL Knob for quicker cutting.
- Models 10, 15 and 20 feature a convenient fold-away reamer.
- Models 65S and 35S are specially designed for stainless steel tubing. Includes 12x (65S) / 6x (35S) individual bearings and a heavy duty cutter wheel to make stainless cutting easier.
- Models 65S features a quick-acting mechanism.



Catalog No.	Model No.	Description	Std. Wheel	Capacity		Weight		Std. Pack
				mm	lb.	kg		
32910	10	Screw Feed Cutter	F-158	3 - 25	¾	0,40	6	
32915	10S	Above w/H-D Wheel (for steel)	E-1240	3 - 25	¾	0,40	6	
32920	15	Screw Feed Cutter	F-158	5 - 28	½	0,68	6	
32925	15S	Above w/H-D Wheel (for steel)	E-1240	5 - 28	½	0,68	6	
32930	20	Screw Feed Cutter	F-158	16 - 54	1¾	0,79	1	
32935	20S	Above w/H-D Wheel (for steel)	E-1240	16 - 54	1¾	0,79	1	
32940	30	Screw Feed Cutter	E-2558	25 - 79	3½	1,60	1	
32950	30S	Above w/H-D Wheel (for steel)	E-2191	25 - 79	3½	1,60	1	
97212	15-SI	Stainless Steel Cutter	E-1525	5 - 28	1½	0,68	1	
29963	35S	Stainless Steel Cutter	E-635	6 - 35	¾	0,40	1	
31803	65S	Stainless Steel Quick-Acting Tubing Cutter	E-635	6 - 65	1½	0,68	1	