

## RE 6 Cable Termination Tool (Utility)



#### Cut wire, crimp connectors and punch boxes with just one tool via the patented RIDGID® QuickChange System™.

- Interchangeable heads allow for tool customization to meet individual needs
- Inline design for easy, one-handed operation, even in tight spots
- 360° head rotation increases accessibility in difficult to maneuver spaces
- Bright white LED light provides direct illumination of your work
- · Built-in sensors and LED indicators ensure tool performance, monitor battery life and indicate when the tool requires service
- · Industry-leading service interval maximizes uptime on the job site
- Rubber overmolded grips for superior comfort and control
- Automatic ram retraction when cutting and crimping
- Nylon straps allow easy tethering or hoisting



### THE RIDGID® RE 6

#### FULLY CUSTOMIZABLE TO MEET YOUR NEEDS.



#### START WITH THE BASE KIT.

Includes RE 6 Tool, two batteries, charger and carrying case.



#### **SPECIFICATIONS**

- · 6-ton hydraulic force output
- Approximate cycle time: 5 seconds
- Service interval: 32,000 cycles
- Temperature limit: 15°F 122°F (10°C 50°C)
- Power: RIDGID® 18V Advanced Lithium Battery platform

CATALOG NO.	DESCRIPTION	WEIG	
52088	RE 6 Electrical Tool Kit (No Heads)	20.8	9,4



#### ORDER THE HEADS YOU NEED FOR THE WORK YOU DO.

**CUTTING HEADS** Select from two different cutting heads.



#### **CU/AL SCISSOR CUTTER HEAD**

• Designed for cutting up to 750 kcmil (MCM) copper/aluminum building wire and 500 kcmil (MCM) copper fine stranded wire

CATALOG NO.	DESCRIPTION		GHT (kg)
47918	SC-60C Cutter Head with Copper/Aluminum Wire Blades	4.75	2,15
47923	Replacement Blades for Copper/Aluminum Wire	0.5	0,23



#### **ACSR CUTTER HEAD**

• Designed for cutting up to 477 kcmil (MCM) ACSR

CATALOG	PERCENTION	WEI	GHT
NO.	DESCRIPTION	(lb.)	(kg)
49408	SC-60C Cutter Head with ACSR Blades	4.75	2,15
47928	Replacement Blades for ACSR	0.5	0,23



#### SWIV-L-PUNCH™ KNOCKOUT PUNCH HEAD

- Punches up to 4" holes in 12 gauge mild steel and 14 gauge stainless steel
- Compatible with knockout punch dies from RIDGID and other manufacturers (sold separately)

CATALOG NO.	OG DESCRIPTION		GHT (kg)
59418	59418 Swiv-L-Punch Knockout Punch Head and Accessories (DrawBolts, Spacers, Thread Adapter & Step Drill Bit)		2,7

#### **CRIMPING HEADS** Select from 4 different crimping heads.







#### **6-TON DIES**

- · Dies clearly marked with color codes to easily match with proper lug
- Fully closing hex crimp profile

	COPPER DIES					
CATALOG NO.	DESCRIPTION					
53548	6T Copper Round Die Se	et				
	Individual dies that co	me in set listed bel	OW.			
CATALOG NO.	DESCRIPTION	CATALOG NO.	DESCRIPTION			
53628	DIE, 6T RD CU 600	53588	DIE, 6T RD CU 2/0			
53623	DIE, 6T RD CU 500	53583	DIE, 6T RD CU 1/0			
53618	DIE, 6T RD CU 400	53578	DIE, 6T RD CU #1			
53613	DIE, 6T RD CU 350	53573	DIE, 6T RD CU #2			
53608	DIE, 6T RD CU 300	53568	DIE, 6T RD CU #4			
53603	DIE, 6T RD CU 250	53563	DIE, 6T RD CU #6			
53598	DIE, 6T RD CU 4/0	53558	DIE, 6T RD CU #8			
53593	DIE, 6T RD CU 3/0					

#### **4PIN™ DIELESS CRIMP HEAD**

 Classified to UL 1976 for copper connectors and wire from #8AWG to 750 kcmil (MCM) and aluminum connectors and wire from #8AWG to 500 kcmil (MCM)

CATALOG NO.	DESCRIPTION	WEI	GHT (kg)
52283	4P-6 4PIN Dieless Crimp Head Only	5.8	2,6

#### **UC-60 CRIMP HEADS**

#### For use With:

- Copper Taps .....#10 Solid 2/0 Stranded
- AL and ACSR Taps ...... #14 Solid 4/0 ACSR
- Stirrups ......#6 4/0 ACSR
- Tension Splices .....#10 Stranded 4/0 ACSR
- Lugs & Splices .....#8-350 MCM AL, 500 MCM CU
- Services Entrances ....... #10 Stranded 4/0 ACSR

CATALOG NO.	DESCRIPTION	WEI	
56793	UC-60 BG, D3/W-Die Crimp Head	4.85	2,20
56798	UC-60 O, D3/W-Die Crimp Head	4.85	2,20

#### **LR-60B LATCHING ROUND CRIMP HEAD**

- Classified to UL 1976 for copper connectors and wire from #8AWG to 600 Kcmil and aluminum connectors and wire from #8AWG to 350 Kcmil
- Compatible with 6-ton dies from RIDGID and other manufacturers.
- LR-60B designed for 6-ton U Dies ONLY

CATALOG NO.	DESCRIPTION	WEI (lb.)	
47753	Latching Round Crimp Head Only**	5.3	2,4

<sup>\*</sup>For the most up to date RIDGID Crimp Die/Electrical Connector Compatibility Charts, go to www.RIDGID.com/CrimpDies

<sup>\*\*</sup>Crimp dies sold separately



	ALUMINUM DIES					
CATALOG NO.	DESCRIPTION					
53553	6T Aluminum Round Die	e Set				
	Individual dies that co	me in set listed bel	OW.			
CATALOG NO.	DESCRIPTION	CATALOG NO.	DESCRIPTION			
53688	DIE, 6T RD AL 350	53658	DIE, 6T RD AL 1/0			
53683	DIE, 6T RD AL 300	53653	DIE, 6T RD AL #1			
53678	DIE, 6T RD AL 250	53648	DIE, 6T RD AL #2			
53673	DIE, 6T RD AL 4/0	53643	DIE, 6T RD AL #4			
53668	DIE, 6T RD AL 3/0	53638	DIE, 6T RD AL #6			
53663	DIE, 6T RD AL 2/0	53633	DIE, 6T RD AL #8			



#### **RE 6 ACCESSORIES**

CATALOG NO.	DESCRIPTION	WEIG	GHT (kg)
46818	RE 6 Tool Only	6.4	2,9
52083	RE 6 Tool Case Only	9.45	4,3
44693	18V Advanced Lithium 2.0Ah Battery	1.0	0,5
44698	18V Advanced Lithium 4.0Ah Battery	1.5	0,7
43458	Advanced Lithium Battery Charger	1.8	0,8
44798	Advanced Lithium Battery Charger Replacement Cord	0.3	0,1





#### Also available from RIDGID®

#### **CABLE CUTTING**



# MC-50 MC-30

#### **RATCHET CABLE CUTTERS**

- · Highest quality blades for maximum durability and longest lifetime
- · Lightweight and compact design for ergonomic use

#### **COPPER/ALUMINUM**

CATALOG	MODEL	CAPACITY	
NO.	NO.	CU	AL
54288	RC-40	600 MCM	750 MCM
54293	RC-55	750MCM	1000 MCM
54298	RC-70	1000 MCM	1000 MCM

#### **ACSR**

Addit						
CATALOG NO.	MODEL No.	CAPACITY ACSR				
59273	RC-336	336 MCM				
59278	RC-556	556 MCM				



CATALOG No.	MODEL No.	CAPACITY CU/AL
54278	MC-30	500 MCM
54283	MC-50	1000 MCM



39-997-158.10

All sales subject to Ridge Tool Company Terms and Conditions of Sales. Catalog Sheet No. R-17-E (1017) Effective Date: October 1, 2017 ©2014, 2017 RIDGID, Inc. The Emerson logo and RIDGID logo are registered trademarks of Emerson Electric Co. or RIDGID, Inc. in the U.S. and other countries.