



706 High CO Analyzer

Features

QUICK AND SIMPLE SET UP All TPI analyzers feature quick and simple set up. Fast purge and the ability to perform fuel selection during start up enable tests to be performed quickly without requiring extra set-up time after initial start-up. TPI analyzers also use the last selected fuel as the default setting. This feature prevents the need to perform fuel selection every time the analyzer is turned on.

- Pump driven for fast response
- Will not shut off if 15 ppm CO is present for increased safety
- Optional A740 IR printer available for hard copies of test results
- Store function to save up to 50 readings
- Push on fittings for fast and easy use
- Large easy to read backlit display

Specifications

Instrument

Operating Temperature Range	14°F to +122°F (-10°C to +50°C)
Battery / Battery Life	AA (3) / > 6 Hours
Display	3 Line Backlit LCD w/ annunciators
Data Storage	50 sets of readings
Time & Date	24 Hour Real Time Clock
Dimensions	7.8" x 3.5" x 2.4"
Weight	1.1lbs

Gas

	Range	Resolution	Accuracy
Carbon Monoxide	0-9,999 ppm	1 ppm	+/- 5 ppm or 5%
Over 9,999ppm displays in percent	1-9.999%	0.001%	+/-5% of reading

706 CO Analyzer



706 Contents

A787 Soft Carrying Case



A763 Mini pump protection filter



A785 Exhaust Probe



Copyright © 2008 Test Products International, Inc.