

Voltage Detector

CPVD275KV

Features

- Non-contact high voltage detector
- Wide range of detection; 80V to 275kV; one instrument fits all applications
- Eight switch-selectable voltage sensitivity ranges
- Lightweight, minimizes sway at the end of long hot sticks
- Audible and visual indication of live voltage
- Self-test ensures that all system functions and indicators are working properly by energizing the complete system
- Designed for use with hot sticks incorporating a shotgun adapter



WARNING: Do not assume conductors are dead or will remain de-energized. Always install proper grounding devices before working.

ELECTRICAL	
Detection Frequency	45 to 70Hz
Ranges	240V, 2kV, 6kV, 11kV, 22kV, 33kV, 132kV, 275kV
Detection	Selection range is detected at approx. 10" (25cm) from the voltage. Greater detection distances can be obtained at lower voltage positions
Power Source	Three 1.5V C cell batteries (included)
Low Battery Indication	_____
MECHANICAL	
Self Test	User selectable
Indicators	Bright red LED and audible buzzer
ENVIRONMENTAL	
Operating Temperature	5° to 130°F (-15° to 55°C)
Storage Temperature	-4° to 150°F (-20° to 65°C)
Humidity	0 to 93% RH @ 104°F (40°C)

Cemenfex

The Safety Tool Specialists

Cemenfex Products, Inc. 650 Jacksonville Road, P.O. Box 1408, Dunwoody, NJ 08016