



TECHNICAL DATA

Features

- Measures inductance, capacitance and resistance
- Autoranging for AC impedance and DE resistance measurement
- Auto LCR smart check and measurement
- Series/Parallel modes
- Ls/Lp/Cp with D/Q/Ø/ESR parameters
- Support DCR mode 200Ω to 200MΩ
- High accuracy with 4 / 5 terminal Kelvin measurement
- 10kHz testing frequency and up to 100kHz output frequency
- Large backlit dual LCD display
- Data hold and relative functions
- Low battery indication with auto power off
- Includes test leads and probes, tweezers, alligator clips and batteries

Model	Description
R5001	LCR Meter
R1020	Fused Test Lead Set
R1210	Alligator Clip Set, Large
CA-05A	Soft Carrying Case
R8888	Hard Carrying Case
R5001-NIST	LCR Meter & NIST

Specifications

Inductance (F=1kHz)

Range: 2000.0μH
20.000/200.0/2000.0mH
20.000/200.00/2000.0H

Resolution: 0.1/1μH
0.01/0.1/1mH
0.01/1H

Accuracy: ±(1.5% +15 dgt.)

Capacitance (F=1kHz)

Range: 2000.0pF
20.000/200.00/2000.0nF
20.00/200.00/2000μF

Resolution: 0.01/0.1/1pF
0.01/0.1/1nF
0.1μF

Accuracy: ±(1.0% +10 dgt.)

Resistance (F=1kHz)

Range: 20.000/200.00Ω
2.0000/20.000/200.00kΩ
2.0000/20.000/200.0MΩ

Resolution: 0.01/0.1/1Ω
0.01/0.1/1kΩ
0.1MΩ

Accuracy: ±(1.5% +5 dgt.)

General Specifications

Test Frequencies: 100/120/1kHz
10kHz
100kHz

Display: Dual LCD display

Relative and Data Hold Functions: Yes

Backlit Display: Yes

Kickstand: Yes

Auto Power Off: Yes (after 5 minutes, off)

Power Supply: 6 AA Batteries

Low Battery Indicator: Yes

Product Certifications: CE

Operating Temperature: 32 to 104°F (0 to 40°C)

Storage Temperature: -4 to 140°F (-20 to 60°C)

Dimensions: 8.6 x 3.7 x 2.4"
(220 x 96 x 60mm)

Weight: 0.8lb (360g)